

Contec Medical Patient Monitor CMS6000



5 Parameters

1. ECG
2. SpO2
3. NIBP
4. Temperature
5. Respiration

Features:

- 8.4" color TFT display.
- Suitable for adult, pediatric and neonatal patient.
- Basic parameters (ECG, SpO2, NIBP, Temperature) in a durable case for bedside monitoring and transport.
- Audible and visual alarms with adjustable alarm ranges.
- Networkable with CONTEC central monitoring system.
- Powerful data management and storage capacity.

ECG

- Lead type: 5-lead
- Input: RA; LA; RL; LL; V
- Sweep speed: 12.5mm/s, 25mm/s, 50mm/s
- Accuracy: $\pm$ bpm or $\pm$ %, whichever is greater.
- Protection: Withstand 4000VAC/50Hz voltage in isolation against electrosurgical and defibrillation.
- S-T detection: YES, Arrhythmia analysis: YES
- Alarm: YES, audible and visual alarm, alarm events recallable.

NIBP

- Method: Oscillometry
- Operation modes: Manual/Automatic/STAT
- Measurement unit: mmHg/KPa selectable
- Measurement types: Systolic, Diastolic, Mean
- Over-pressure protection: YES

SpO2

- Measurement range: 0-100%
- Accuracy: $\pm$ 2digit (70~100%);
- 0~69% unspecified

Temperature

- Resolution: 0.1
- Channel: Dual-channel
- Alarm range: 0-50

Standard Configuration:

◇ ECG, NIBP, SpO2, TEMPERATURE

Optional:

◇ RESP, 2-TEMP, 2-IBP, ETCO2, Network, Thermal Recorder

